

CONSUMPTION TABLET

PREMIUM WOOD-/SURFACE PROTECTION

Deck

Access varies because of how accurate it is and how dry the wood is, when drier wood draws more.

m²	SiOO:X WOOD PROTECTION DECK Ca consumption 2 strokes	SiOO:X SURFACE PROTECTION DECK Ca consumption One stroke
4-5	1 lit	5 dl
8-10	2 lit	1 lit
20-25	5 lit	2,5 lit
30-40	8 lit	4 lit
40-50	10 lit	5 lit
60-75	15 lit	7,5 lit
80-100	20 lit	10 lit
100-125	25 lit	13 lit

Consumption on older wood

1 year ca 10%
2 years ca 20%
3 years ca 25%
8 < years 30-35%

CONSUMPTION TABLET

PREMIUM WOOD-/SURFACE PROTECTION

Panel

Applies to fine sawned panels

For panels vertical surfaces are recommended.

m²	SiOO:X WOOD PROTECTION PANEL Ca consumption 2 strokes	SiOO:X SURFACE PROTECTION PANEL Ca consumption One stroke
15–20	5 lit	2,5 lit
30–40	10 lit	5 lit
45–60	15 lit	7,5 lit
60–80	20 lit	10 lit
90–120	30 lit	15 lit
120–160	40 lit	20 lit

Consumption on older wood

1 år ca 10%

2 år ca 20%

3 år ca 25%

8 < år 30–35%